


# Bolphane® BX

Multipurpose Shrink Film

- High degree of shrink force, ideal for multipacking applications.
- Excellent stiffness and flatness particularly adapted for singlewound applications.
- Broad sealing characteristics, including static sealing.
- Superior optics

## APPLICATIONS

➔ Due to its very good mechanical properties, Bolphane BX is a versatile film, which is able to run on a variety of machines and equipment for all types of applications.



➔ Its stiffness and lay flat, combined with good tensile strength make BX the ideal product for multipacking application. Excellent gloss and clarity add to its presence.

[Info@iipackaging.com](mailto:Info@iipackaging.com)


Bolloré



# Bolphane® BX

## TENSILE STRENGTH

- Versatile, BX offers higher tensile strength and stiffness at equivalent thickness.



## TECHNICAL FEATURES

PROPERTIES	50 GAUGE	60 GAUGE	75 GAUGE	100 GAUGE
Yield (MSI per pound)	59,3	51,4	40,6	30,9
Gloss (85°) (%)	118			
Haze (%)	2,5			3
Free Shrink (%) at 200°F	20			
at 250°F	50			
Seal strength (g/inch)	1600	2 000	2 100	2 300
WVTR (gms/100 sq.in/24 hrs at 95% HR, 95°F)	1,0	0,9	0,7	0,5
O <sub>2</sub> Permeability (cc/m <sup>2</sup> /24 hrs at 73°F, 1 atm)	8500	7 000	5 500	4 000
Length of the roll (Ft) Singlewound BX-SW	10500	8 750	7 000	5 250
Centerfolded BX-CF	5250	4 375	3 500	2 625
Core Internal Diameter (inch)	3"			
Nominal roll outside diameter (inch)	9" 1/2			

## STANDARD PUT-UPS

- Bolphane BX is available in Singlewound (BX-SW) or in Centerfolded (BX-CF). For any other requirement, please contact us.

TYPE	WIDTH (inch)		
	mini	maxi	increment
BX-SW		78"	1/4"
BX-CF		40"	1"